

VersaLog™

SiteView Software



Supports USB, serial port and Ethernet connections for easy local and remote access

Downloads multiple data loggers simultaneously

Custom equation and custom-line equation solves scientific and laboratory algorithm difficulties

Displays both the tabular data view and the plot view

Zooming in /zooming out function provides detailed view of data

Real-time viewing and chart recording replaces the paper chart recorder

SiteView is a Microsoft Windows based application which works with VersaLog Series data loggers for downloading, configuration, data analyzing and plotting.

Its user-friendly graphic interface plus powerful functionalities fit both novice and advanced users.

The versatility of the custom equation and custom-line equation handle complicated measurement requirements.

Technical specifications (subject to change without notice)

System Requirements

Computer	CPU: 1.0 GH or above, Memory: 256K or above, Port: 1 USB port or 1 COM port (SL-RS232 required), Hard Drive: 1GB or above
Operating System	Windows XP, Vista, 7, 8, 10
	Voltage channels: +/- 0.05% FSR @ 25°C for 20V channels, +/- 0.1% FSR @ 25°C for 2V channels

Communications

Supported Interfaces	USB, Serial Port, Ethernet (USB Device Server, Serial Device Server)
Baud Rate	Auto-detected baud rate from 2400 to 115200 bps

Logger Interactions

Status View	View status of the connected logger
Configuration	Configure logger for new recording session
Real-Time View	Monitor logger in real-time list view and chart view; real-time data can be saved to time stamped text files

Plotting

Views	Tabula, graph view , statistics
Configuration	Configure axis, lines, view properties
Zoom	Zoom in/zoom out, scale zoom, box zoom, time-span zoom
Labels & Annotations	Add, edit, delete graph labels and line annotations
Custom Line	Add, edit, delete the custom line
Custom Channel	Add, edit, delete the custom channel

Measurement Conversion

Custom Equation	Add, edit, delete the custom equation
Custom Line Equation	Add, edit, delete the custom-line equation
Unit	Add, edit, remove unit categories and units
Baud Rate	300 to 115,200

Data Importing/Exporting

SiteView File	Load single or multiple SiteView files into one viewport. Export plot to images: Emf, PNG, Gif, Jpeg, Tiff and Bmp file format. Export plot to text: csv, txt. Save multiple SiteView files to single SiteView file. Print plot, tabular data, statistics.
Equations & Units	Import, Export Equation files and Unit files

Help

Interactive Help	Related help topic is displayed with hot key (F1)
Help File	Portable Document Format (.PDF), Microsoft Compiled HTML Help (.CHM)

[1]: Maximum enabled channel: 1 for 20ms interval, 2 for 30ms, 8 for 40ms or bigger interval.
 [2]: Sold separately.

DISTRIBUTED BY
CAS **DATALOGGERS**

8437 Mayfield Rd., Unit 104A
 Chesterland, OH 44026
 T: 800.956.4437
 F: 440.729.2586
 sales@dataloggerinc.com

dataloggerinc.com