

AERINOS™

ADS-300 NBloT/LTE-M RTU



Introduction

ADS-300 is an ultra low power NBloT/LTE-M End Node with multiple sensor support. The unit incorporates a built in modem, a USB serial port, 1 digital input/counter, an analog input, an optional 3-axis digital accelerometer, a Coulomb meter and multiple excitation options for powering and measuring transducers. The device supports acquisition of up to 8 measurement channels, based on the popular SDI-12 communication protocol and additional 8 channels, based on the MODBUS protocol. An ultra low power microcontroller is utilized for data sampling, subsystem activation and overall system control. The unit incorporates a Lithium Thionyl battery supplying system operation for up to 10 years.

Modes of operation

Modes of operation include autonomous battery operation or power supply through the USB port for unit configuration. During battery supplied operation, only the low power microcontroller is awake. The microcontroller activates the modem during data transfer, as well as other subsystems for sampling and logging.



Features

- Power network independent NBloT/LTE-M End Node
- Up to 10 years maintenance free operation
- Quick and easy installation
- 1 digital input/counter, 1 analog input, internal 3-axis digital accelerometer (optional), Built in battery monitoring, SDI-12 and MODBUS sensor data acquisition
- Several excitation options for external sensors

Applications

- Security systems
- Power network, Cable fault monitoring
- Building Management & Home Automation
- Oil & Gas distribution
- Asset management
- Greenhouse controls & irrigation systems
- M2M systems

Technical characteristics

| | |
|-----------------------|---|
| Power supply | |
| Battery | Internal 13.0 Ah Lithium Thionyl |
| External | 5V (USB power) |
| Consumption | 20µA max (Low power operation) 2 mA (AI sampling w/o sensors) ~50mA (Alarm messaging) |
| Digital inputs | 1, 0-30VDC or potential free contact inputs |
| Analog inputs | 1, 0-1V, 12 bit resolution |
| Counters | 1, kHz max. |
| Transducer Excitation | 5VDC/200mA or 12VDC/200mA max. |
| Serial port | USB serial, 9600 to 115200 bps |
| Modem | LTE Cat-M1/NBloT with 2G fallback, Sierra Wireless HL Series 78xx |
| Antenna | internal or external, 4G LTE |
| Indications | 2 LED, network status, device status |
| Temperature | -40°C...+70°C operating |
| Protection | IP66 |
| Dimensions | 124 x 79.5 x 70 mm, (with cable gland) |
| Weight | 0.3 kg (w/o Battery) |

Data Acquisition

Sampling period and data send rate are user defineable. Ultra low power standby mode followed by frequent data recording and transmission can be selected to fit the application needs, while maximizing the battery life.

SDI-12 Serial Bus

ADS-300 is compliant to the SDI-12 Standard Version 1.2 and supports extended commands for sensor configuration, in terminal mode. ADS-300 can collect data from several SDI-12 sensors for a total amount of 8 measurement channels.

RS-485 Serial Bus (MODBUS)

ADS-300 supports acquisition from sensors with RS-485 interface using the MODBUS protocol.

Transducer excitation

A user adjustable 5V/12VDC excitation output is available for powering low power external sensors.

Tilt Sensing

The unit has an optional accelerometer which is used for measuring angle declination.

Coulomb Meter

A user enabled Coulomb Meter allows for the monitoring of the battery's consumption.

Setup and programming

The unit can be programmed locally through the serial by using simple ASCII configuration commands. The command set features commands for configuring scaling and timing parameters.

Enclosure

Plastic enclosure (IP66/68) for in- and outdoor use.

Firmware features

| | |
|---------------------------|---------------------------------|
| Digital input alarm state | Transition selection |
| Analog input | Scale, gain selection |
| Accelerometer | Tilt Sensing |
| SDI-12 | Compliant to SDI-12 Version 1.2 |
| MODBUS | MODBUS ASCII protocol |
| Sampling interval | 1-255 minutes |
| Sensor warm-up time | 1-255 sec |
| Transmission rate | 0-255 hours |
| Programming | ASCII command set |
| Local setup | via USB serial port |

Ordering information

| | |
|------|---------|
| Code | ADS-300 |
|------|---------|



Infinite Informatics, Ltd.
1, Valaoritou Street
GR-54626 Thessaloniki, Greece
Phone: +30-2310-553545,
Fax: +30-2310-552006
Email: sales@indinf.gr
URL: www.infinite.com.gr, www.indinf.gr

Representative - authorized dealer

CAS DataLoggers
8437 Mayfield Rd, Unit 104A
Chesterland, OH 44022
Phone: (800) 956-4437
Fax: (440) 729-2586
Email: sales@dataloggerinc.com
URL: www.dataloggerinc.com